

Inhaltsverzeichnis		1+2-part leaning ladder (8006, 8236)	9
Company presentation	3	2-part combination ladder (8216)	10
Rise-Tec – <b>Red Label</b>	4	3-part combination ladder (8226)	11
Step ladders (8616)	5	Rise-Tec – <b>Yellow Label</b>	12
Footsteps (8636, 8646)	6	1-part leaning ladder (8007)	13
Leaning step ladder (8606	7	2-part leaning ladder (8207)	14
Standing step ladder (8676)	8	3-part combination ladder (8217)	15

### We are at your service:



#### Sales team



Chief executive office Stefan Hassler Tel. 0 64 34 / 20 79 862 e-mail: sh@rise-tec.de

External sales

Karsten Nemack

Tel. 0 64 34 / 20 79 862

e-mail: kn@rise-tec.de



Chief executive office Heiko Hassler Tel. 0 64 34 / 20 79 860 e-mail: hh@rise-tec.de



Customer care Judith Schnappinger Tel. 0 64 34 / 20 79 861 e-mail: js@rise-tec.de

#### **Production team**



Production scheduling Sebastian Lauer



Member of production Holger Lauth



Member of production Rene Reuß



# Two brothers – one team – the top product

We, Stefan and Heiko Hassler, two brothers from the company HACA Leitern, have founded together with our dedicated team the company Hassler & Hassler GmbH u. Co. KG located on the premises of our family company Lorenz Hasenbach GmbH u. Co. KG (HACA).

#### How does this fit together?

More than 130 years of experience, affectionate family tradition and well-grounded know-how in combination with fresh, new and own ideas of a younger generation, have generated a totally new range of products only available for the specialised trade. And all of this is united "under one umbrella".

#### That is how the brand Rise-Tec was born.

With the brand Rise-Tec we want to combine the known quality standard of HACA Leitern with new innovations.

Rise-Tec are aluminum ladders for the professional but also private use, being even more safe, even more stable and even more long-lasting.

#### Our stile profile is the key!

The previous standard stile of a ladder is a rectangular hollow profile. But there are other shapes, granting way more resistance against dents and buckles.

We used this to our advantage in order to offer a higher safety against rupture.

We call this the "Punch-Resist-Effect"!

These profiles, which are unique in Germany, became the basis for our products.



#### How does the Punch-Resist-Effect present itself in practice?

If you work with ladders daily you will surely know, how often it happens; a tool or component falls onto the ladder stile, the ladder slips and hits an edge or the stile gets a shock during transport.

Have you as well been astonished how deep a dent or buckle can be from such an impact?

Did you also know that at that spot, with conventional, rectangular aluminum stile profiles, the ladder structure is weakened and can break some day without any warning?

Often you do not pay attention to it and just go on – with the correspondent risk of an accident. The consequences can be damages to persons and property and work stoppage. Furthermore, often liability insurances and employers' liability insurance associations have to be involved as well.

Contrary to that, with the "Punch-Resist-Effect", which results from the shape of our innovative stile profile, we have achieved that a Rise-Tec ladder remains stable, in the truest sense of the word.

Damages caused by tools or shocks, as described above, are normally endured without essential weakening of the aluminum structure, so you can proceed with work safely!

Rise-Tec Leitern – Da steh' ich drauf!

Hus les Stefan Hassler




### **Red Label**

The ladder for professional use at an affordable price.

The double delta profile, which is unique in Germany, combined with a special aluminium alloy makes it possible to use it under special loads. The profile is used for the stepladders of the Red Label. For the rung ladders of this series we also use a specially developed double T-profile

Both profiles increase resistance to dents and buckles because of the PUNCH-RESIST-EFFECT





Manufactured in accordance with DIN EN 131, they correspond to the "Professional class". In terms of stability and longevity, the standard specifications are even exceeded by far. A reliable "colleague" for your professional life.

### Red Label is available in the following variants:

step ladder:

- stepladder with safety bridge and storage tray
- steps in various widths

rung ladder:

- 1-part leaning ladder
- 2-part leaning ladder
- 2-part combination ladder
- 3-part combination ladder

#### Benefi -increasing details:

- oresistance against dents and buckles with the **PUNCH-RESIST-EFFECT**
- extra wide rungs (35x35mm) and 80mm steps for comfortable, safe standing
- rungs and steps with ribbing increase the slip resistance
- flanged connection from stile to rung and step as a permanently stable connection
- extremely anti-slip ladder feet, replaceable after wear and tear

#### Accessories:

- handrails for stepladders
- safety steps for stepladders increase the standing area to 130mm and are simply clipped on.
- brake rollers for footsteps
- safety bar for steps
- hooks and suspension devices for stepladders

www.rise-tec.de




# Step ladder with safety bridge 8616

**Red Label** 

- one sided
- highest stile stability against buckling
- useful storage tray for assembly material, tools, etc.
- ergonomically designed aluminium stiles
- very appealing design
- platform 33.5x25.5cm
- step depth 80mm

article number	amount of steps	length of stile (cm)	height (cm)	bottom width of the ladder (cm)	depth (cm)	weight (kg)
8616000003	3	150	70	48	71	5.5
8616000004	4	176	95	51	90	7
8616000005	5	202	120	54	106	8
8616000006	6	231	145	58	123	9
8616000007	7	259	170	61	139	10.5
8616000008	8	286	195	65	158	12
8616000010	10	340	245	72	193	16
8616000012	12	394	295	79	228	19





#### Accessories/Spare parts:

floor protectors for ascending part



0861600100

floor protectors red supporting part



0861600200

handrail, small, incl. assembly material



0861100100 amount of steps 03-06

handrail, medium, incl. assembly material



0861200100 amount of steps 07-08

handrail, large, incl. assembly material



0861300100 amount of steps 10-12

clip-on safety step 130x325mm



0860240100

clip-on safety step



0860260100

### Footstep 8636

- narrow step, top platform 250x405mm
- according to DIN EN 14183-B
- access from both sides
- highest stile stability against buckling
- ergonomically designed aluminium stiles
- very appealing design
- foldable spreader lock for space-saving storage and easy transport
- step depth 80mm

article number	amount of steps	length of stile (cm)	height (cm)	bottom width of the ladder (cm)	depth (cm)	weight (kg)
8636000002	2	54	45	46	59.4	4
8636000003	3	81	70	49	79.6	5.5
8636000004	4	108	95	53	99.9	7.5



**Red Label** 

#### **Accessories/Spare parts:**

floor protectors for ascending part



0861600100

6

handrail, medium, incl. assembly material



0861200100 amount of steps 03-04

clip-on safety step



0860240100

brake rollers for steps



0054110000

safety railing



0861010011 amount of steps 02-04

### Footstep 8646

- very wide step, top platform 250x650mm
- according to DIN EN 14183-B
- access from both sides
- highest stile stability against buckling
- ergonomically designed aluminium stiles
- very appealing design
- foldable spread locker for space-saving storage and easy transport
- step depth 80mm

article number	amount of steps	length of stile (cm)	height (cm)	bottom width of the ladder (cm)	depth (cm)	weight (kg)
8646000002	2	54	45	70	59	5.8
8646000003	3	81	70	74	78	7.5

### 8646000004 108 95 96 9.4

### **Accessories/Spare parts:**

floor protectors for ascending part



0861600100

handrail, medium, incl. assembly material



0861200100 amount of steps 03-04

clip-on safety step 130x325mm



0860240100

brake rollers for steps



0054110000

**Red Label** 



safety railing



0861010013 amount of steps 02-04



**Red Label** 

# **Step leaning ladder 8606**

- highest stile stability against dents and buckles ergonomically designed aluminium stiles
- very appealing design
- hooks available as accessories
  - (1 pair is included in the scope of delivery from 11 steps on)
- outer ladder width 430mm
- clear width 384mm
- step depth 80mm



article number	amount of steps	length of stile (cm)	weight (kg)
8606000005	5	155	3.7
8606000006	6	182	4.6
8606000007	7	209	5.3
8606000008	8	236	6
8606000009	9	263	6.7
8606000010	10	290	7.5
8606300011	11	317	8
8606300012	12	344	8.9
8606300013	13	371	9.5

#### **Accessories/Spare parts:**

floor protectors 1 pair



0861600100

handrail, small, incl. assembly material



0861100100 amount of steps 05-07

handrail, medium, incl. assembly material



0861200100 amount of steps 08-09

handrail, large, incl. assembly material



0861300100 amount of steps 10-13

clip-on safety step 130x325mm



0860240100



0528460100

hooks for step ladders,



09103600100

DA STEH' ICH DREAUF!

highest stile stability against dents and buckles

ergonomically designed aluminium stiles

very appealing design

sizes 2, 3 and 4 can also be used as footstep, as it is equipped with a foldable spreader lock (according to DIN EN 14183-B)

platform 35.5x24.5 cm

step depth 80mm



### **Red Label**



article number	amount of steps	length of stile (cm)	height (cm)	bottom width of the ladder (cm)	depth (cm)	weight (kg)
8676000002	2	57	46	42	59,.	3.4
8676000003	3	77	70	46	79.6	5
8676000004	4	100	95	50	99.9	6.3
8676000005	5	129	120	51	120.1	8
8676000006	6	156	145	54	140.3	10
8676000008	8	210	195	61	180.8	13
8676000010	10	264	245	68	221.6	17
8676000012	12	318	295	74	261.7	20

### **Accessories/Spare parts:**

floor protectors 1 pair



0861600100 for ascending part

handrail, medium, incl. assembly material



0861200100 amount of steps 03-06

handrail, large, incl. assembly material



0861300100 amount of steps 08-12

clip-on safety step 130x325mm



0860240100

clip-on safety step 130x585mm



0860260100

safety railing



amount of steps 02-04

brake rollers for steps



0054110000 amount of steps 02-04



## 1-part leaning rung ladder 8006

- strong and very stable double-T-profile
- highest stile stability against buckling
- robust, consistently stable multiple crimping
- comfortable and safe standing position due to 35mm deep rungs
- clear width 360mm
- outer ladder width 400mm
- rung dimension 35x35mm
- rung distance 300mm

article number	amount of rungs	length of stile (cm)	length of the stabiliser (cm)	weight (kg)
8006000006	6	180		3.2
8006000007	7	210		3.8
8006000008	8	240		4.3
8006000009	9	270		4.8
8006050010	10	300	100	8.1
8006050012	12	360	100	9
8006050013	13	390	100	9.7
8006050014	14	420	100	11.3
8006050016	16	480	100	12.7
8006050017	17	510	100	13.5



### **Red Label**

#### **Accessories/Spare parts:**

floor protectors red for stiles, 55x28mm



0800600100 amount of rungs 06-17



0189011300



## 2-part extension ladder wthout rope 8236

- strong and very stable double-T-profile
- highest stile stability against buckling
- robust, consistently stable multiple crimping
- for size 8 each ladder part can be used individually
- hooks with anti-derail device
- comfortable and safe standing position due to 35mm deep rungs
- clear width 360mm
- outer ladder width 470mm
- rung distance 300mm
- rung dimension 35x35mm

article number	amount of rungs	length in extended version (cm)	length in telescopic version (cm)	length of the stabiliser (cm)	weight (kg)
8236050006	6+6	320	200	100	8.8
8236050008	8+8	410	260	100	10.8
8236050010	10+10	530	320	120	15
8236050012	12+12	650	380	120	22.8

#### **Accessories/Spare parts:**

floor protectors for stiles, 55x28mm

floor protectors for stiles, 78x22mm







0800600200 amount of rungs 12



0189011300

## **Red Label**





# 2-part combination ladder 8216

- can be used as standing and leaning ladder
- strong and very stable double-T-profile
- highest stile stability against buckling
- robust, consistently stable multiple crimping
- very appealing design
- hooks with anti-derail device
- comfortable and safe standing position due to 35mm deep rungs
- clear width 400mm
- outer ladder width 470mm
- rung distance 300mm
- rung dimension 35x35mm





	as leaning		ıg ladder	g ladder as standing ladder			
article number	amount of rungs	length in extended version (cm)	length in telescopic version (cm)	largest vertical height (cm)	top permissible standing height (cm)	length of the stabiliser (cm)	weight (kg)
8216000006	6+6	320	200	188	115	100	8.8
8216000008	8+8	410	260	244	171	100	10.8
8216000010	10+10	530	320	300	227	120	15
8216000012	12+12	650	380	356	283	120	22.8

#### **Accessories/Spare parts:**

floor protectors for stiles, 55x28mm

floor protectors for stiles, 78x22mm







0800600100 amount of rungs 06-10

0800600200 amount of rungs 12

0189011300



**Red Label** 

3-part extension ladder without rope 8226

can be used as standing and leaning ladder

strong and very stable double-T-profilehighest stile stability against buckling

robust, consistently stable multiple crimping

very appealing design

for size 8 each ladder part can be used individually

with castors at the top end

hooks with anti-derail device

comfortable and safe standing position due to 35mm deep rungs.

clear width 360mm

outer ladder width 540mm

rung distance 300mm

rung dimension 35x35mm





		as leanir	ıg ladder	:	as standing lad	der		
article number	amount of rungs	length in extended version (cm)	length in telescopic version (cm)	smallest vertical height (cm)	largest vertical height (cm)	top permissible standing height (cm)	length of the stabiliser (cm)	weight (kg)
8226000008	8+8+8	560	262	245	379	244	120	23.2
8226000009	9+9+9	650	292	273	437	300	120	25.8
8226000010	10+10+10	680	322	300	465	328	120	27.8

#### **Accessories/Spare parts:**

floor protectors for stiles, 55x28mm



0800600100 amount of rungs 08-10 floor protectors for stiles, 78x22mm



0800600200 amount of rungs 08-10



0189011300



### Yellow Label

Our inexpensive aluminum ladders "Yellow Label": ideal for the demanding user for hobbies, at home, in the office and for occasional use.

The Yellow Label is purely a rung ladder series. The C-profile used here increases the resistance to dents and buckles because of the PUNCHERESIST-EFFECT



Manufactured in accordance with DIN EN 131, they correspond to the "Professional class".

#### Yellow Label is available in the following variants:

- Ladders with rungs
- 1-part single ladder
- 2-part single ladder
- 2-part combination ladder

#### Benefi -increasing details:

- eresistance against dents and buckles because of the **PUNGH-RESIST-EFFECT**
- rungs and steps with ribbing increase the slip resistance
- the rungs have a dimension of 30x30mm
- flanged connection from stile to rung as a permanently stable connection
- extremely anti-slip ladder feet, replaceable after wear and tear
- light weight



Yellow Label

# 1-part rung leaning ladder 8007

- made of strong aluminium C-stile-profile
- orobust aluminium rungs with a depth of 30mm
- highest stile stability against bucklingouter ladder width 400mm
- clear width 350mm
- rung dimension 30x30mm
- rung distance 300mm

article number	amount of rungs	length of stile (cm)	length of the stabiliser (cm)	weight (kg)
8007000006	6	180		2.4
8007000007	7	210		2.8
8007000008	8	240		3.2
8007000009	9	270		3.6
8007050010	10	300	100	6.7
8007050011	11	330	100	7.1
8007050012	12	360	100	7.5
8007050013	13	400	100	8.7

# **Accessories/Spare parts:** floor protectors for

stiles, 60x25mm



0821700100 amount of rungs 06-13



- made of strong aluminium-C-profile
- orobust aluminium rungs with a depth of 30mm
- highest stile stability against buckling
- solid aluminium fittings
- clear width: 420mm and 350mm (respectively)
- outer ladder width: 470mm and 400mm (respectively)
- rung dimension 30x30mm
- rung distance 300mm

article number	amount of rungs	length in extended version (cm)	length in telescopic version (cm)	length of the stabiliser (cm)	weight (kg)
8207000006	6+6	284	199		8.8
8207050008	8+8	404	257	100	10.4
8207050010	10+10	524	315	100	16
8207050011	11+11	584	344	120	20

### **Accessories/Spare parts:**

floor protectors for stiles, 60x25mm



0821700100 amount of rungs 06-08

floor protectors for stiles, 75x25mm



0821700200 amount of rungs 10-11



**Yellow Label** 




Yellow Label

# 2-part combination ladder 8217

- can be used as standing and leaning ladder
- made of strong aluminium-C-profile
- highest stile stability against buckling
- orobust aluminium rungs with a depth of 30mm
- solid aluminium fittings
- clear width: 420mm and 350mm (respectively)
- outer ladder width: 470mm and 400mm (respectively)
- rung dimension 30x30mm
- rung distance 300mm

			as leaning ladder		as standing ladder			
article number		amount of rungs	length in extended version (cm)	length in telescopic version (cm)	largest vertical height (cm)	top permis- sible standing height (cm)	length of the stabiliser (cm)	weight (kg)
82170	000006	6+6	284	199	184.5	112	100	8.8
82170	80000	8+8	404	257	241.5	161	100	10.4
82170	000010	10+10	524	315	298.5	220	100	16
82170	000011	11+11	584	344	327	249	120	20





floor protectors for stiles, 60x25mm



0821700100 amount of rungs 06-08

floor protectors for stiles, 75x25mm



0821700200 amount of rungs 10-11





Our production facility in Bad Camberg

Hassler & Hassler GmbH u. Co. KG Dieselstr. 14, 65520 Bad Camberg Tel. 0 64 34 / 20 79 860 www.rise-tec.de info@rise-tec.de